

Elliott Electric Supply

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr. 75964-0000, TX Nacogdoches Phone: 936-569-7941 Fax: 936-560-4685



FRSR1712 17-1/2A 600V TD Class RK5 Dual Elem Fuse-Fusetron Bussmann Fuses

Catalog Number	FRSR1712
Manufacturer	Bussmann Fuses
Description	Eaton Bussmann Series FRS-R Fuse, 17.5 A, Dual, Class RK5,
	Non-Indicating, Ferrule End X Ferrule End, 10 Sec At 500%, 200
	Kaic At 600 V, 20 Kaic At 300 VDC, Standard, 600 V, 300 VDC
Weight per unit	
Product Category	Dual Element
Features	
amperage rating	17.5 A
class	Class RK5
connection	Ferrule End X Ferrule End
dimensions	5.0000 IN X 0.8100 IN X 0.8100 IN
element	Dual
interrupt rating	200 kAIC at 600 Vac20 kAIC at 300 Vdc
media	Yes
Response Time	10 S at 500%
Voltage Rating	600 Vac, 300 Vdc
Dimensions and Weight	
Size	0.81 In Diameter X 5.00 In Length
Descriptions	
Description	17-1/2A 600V TD CLASS RK5 DUAL ELEM FUSE-FUSETRON
extra long description	BUSS FRS-R-17-1/2 FUSETRON DUAL ELE
Features	Bussmann's UL Class RK5 Fusetron product offering provides
	energy efficient advanced protection with its dual-element,
	time-delay construction and is available with optional open fuse
	indication on select ratings. Available in both 250Vac and
	600Vac, 200kA RMS Sym interrupting rating and sizes ranging
	from 0 to 600 amp. Fusetron's deliver 10 seconds (minimum) of
	time-delay at 500% of rated current (8 seconds for 1/10-30A
	sizes).
Long Description	Eaton Bussmann series FRS-R fuse, 17.5 A, Dual, Class RK5,
	Non-indicating, Ferrule end x ferrule end, 10 sec at 500%, 200
	kAIC at 600 V,20 kAIC at 300 Vdc, Standard, 600 V, 300 Vdc
Product Type	Fusetron Dual Element Fuse Class RK5
Special Features	Renewable



ELLIOTT ELECTRIC SUPPLY 2310 N. Stallings Dr. 75964-0000, TX Nacogdoches Phone: 936-569-7941 Fax: 936-560-4685

	Inform	

Brand	Eaton
GTIN	00051712508315
Manufacturers Part Number	FRS-R-17-1/2
UPC	051712508315

Taxonomies, Classifications, and Categories

Category Description	Fuses & Fuse Accessories
Type	FUSF

Packaging

Carton	10	
Weight Per each	0.16	

Uses, Certifications, and Standards

Application	Ind Facilities & Factories - Facility: Safety and Security Systems
standard	CE Marked