



ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr.
75964-0000, TX Nacogdoches
Phone: 936-569-7941
Fax: 936-560-4685

RX142WG1000 14/2 WG Romex-1000' *Southwire Company*



Catalog Number	RX142WG1000
Manufacturer	Southwire Company
Description	Southwire® Romex® Brand Simpull® NM-B (Nonmetallic-Sheathed) Cable May Be Used For Both Exposed and Concealed Work In Normally Dry Locations At Temperatures Not to Exceed 90°C (With Ampacity Limited to That For 60°C Conductors) As Specified In The National Electrical Code. NM-B Cable Is Primarily Used In Residential Wiring As Branch Circuits For Outlets, Switches, and Other Loads. NM-B Cable May Be Run In Air Voids Of Masonry Block or Tile Walls Where Such Walls Are Not Wet or Damp Locations. Voltage Rati
Weight per unit	0.0580 (lbs/ft)
Product Category	NM-B - NMD90

Features

strands	1
---------	---

Dimensions and Weight

Length	1621
--------	------

Descriptions

Also Known As...	220 Wire Thermoplastic-Sheathed Cable Non-Metallic Sheathed Cable
Description	14/2 WG ROMEX-1000'
extra long description	SWC 28827401 14-2 CU NM-B W/G
Long Description	Southwire® Romex® Brand SIMpull® NM-B (nonmetallic-sheathed) cable may be used for both exposed and concealed work in normally dry locations at temperatures not to exceed 90°C (with ampacity limited to that for 60°C conductors) as specified in the National Electrical Code. NM-B cable is primarily used in residential wiring as branch circuits for outlets, switches, and other loads. NM-B cable may be run in air voids of masonry block or tile walls where such walls are not wet or damp locations. Voltage rati
similar brands	Romex®



ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr.
75964-0000, TX Nacogdoches
Phone: 936-569-7941
Fax: 936-560-4685

Manufacturer Information

Brand	Copper
GTIN	00032886263019
UPC	032886263019

Taxonomies, Classifications, and Categories

Category Description	ROMEX (RX)& UF CABLE
----------------------	----------------------

Availability

minimum qty	1000
-------------	------

Packaging

Carton	1000
Weight Per foot	0.058